





# DRIE

## TRANSFORMATOREN BV



### MAATVOERING RINGKERNTRANSFORMATOREN



CE

Ringkerntransformatoren ingegoten in kunststof beker

Type	Vermogen	Afmetingen in ca. mm.			Totaal Gewicht ca. Kg
		A	H	i	
RK-ISS/10	10 VA	63	30		0,55
RK-ISS/20	20 VA	62	35		0,80
RK-ISS/35	35 VA	81	39		0,81
RK-ISS/50	50 VA	81	39		0,80
RK-ISS/60	60 VA	81	47		0,94
RK-ISS/75	75 VA	88	45		1,06
RK-ISS/80	80 VA	96	47		1,10
RK-ISS/100	100 VA	96	45		1,35
RK-ISS/125	125 VA	105	45		1,40
RK-ISS/160	160 VA	116	53		1,95
RK-ISS/200	200 VA	116	53		2,25
RK-ISS/250	250 VA	126	52		2,55
RK-ISS/300	300 VA	126	65		3,30
RK-ISS/400	400 VA	140	65		4,17

MAATVOERING EN GEWICHTEN ONDER VOORBEHOUD.

RING

DRIE Transformatoren BV, Postbus 55, 6980 AB DOESBURG, Tel.: 0313 - 41 55 00  
Fax: 0313 - 41 22 77; Intern.: [www.drietrafo.com](http://www.drietrafo.com) ; E-mail: [info@drietrafo.com](mailto:info@drietrafo.com).