




### MAATVOERING RINGKERNTRANSFORMATOREN



### Open Ringkerntransformatoren

Type	Vermogen	Afmetingen in ca. mm.			Totaal Gewicht ca. Kg.
		A	H	i	
RK-ISS/10	10 VA	58	28		0,35
RK-ISS/20	20 VA	55	32		0,64
RK-ISS/35	35 VA	70	34		0,65
RK-ISS/50	50 VA	73	35		0,64
RK-ISS/60	60 VA	75	42		0,85
RK-ISS/75	75 VA	75	44		0,88
RK-ISS/80	80 VA	76	46		0,92
RK-ISS/100	100 VA	95	40		1,20
RK-ISS/125	125 VA	95	40		1,23
RK-ISS/160	160 VA	105	45	28	1,52
RK-ISS/200	200 VA	110	48		1,92
RK-ISS/250	250 VA	120	50		2,35
RK-ISS/300	300 VA	120	60		2,90
RK-ISS/400	400 VA	130	62		3,60
RK-ISS/500	500 VA	138	66		3,96
RK-ISS/630	630 VA	145	78		5,00
RK-ISS/800	800 VA	162	69		6,10
RK-ISS/1000	1,0 KVA	165	82		7,40
RK-ISS/1300	1,3 KVA	182	86		9,30
RK-ISS/1600	1,6 KVA	200	95		11,0
RK-ISS/1900	1,9 KVA	210	95		13,1
RK-ISS/2200	2,2 KVA	230	85		14,9
RK-ISS/2500	2,5 KVA	200	100		16,2

MAATVOERING EN GEWICHTEN ONDER VOORBEHOUD.

ROBO